

10/564841

IAP20 Rec'd PCT/PTO 12 JAN 2005



AMENDMENT

(amendment based upon the provision of Article 11 of said Law)

To: Examiner of the Patent Office

1. Identification of the International Application

PCT/JP2004/012776

2. Applicant

Name: CANON KABUSHIKI KAISHA

Address: 3-30-2, Shimomaruko, Ohta-ku, Tokyo
146-8501 Japan

Country of Nationality: JAPAN

Country of Residence: JAPAN

3. Agent

Name: (10149) Patent Attorney

OCHI, Takao



Address: No. 602, Fuji Bldg., 2-3, Marunouchi 3-chome,
Chiyoda-ku, Tokyo 100-0005 Japan

4. Item to be amended: Description and Claims

BEST AVAILABLE COPY

5. Subject Matter of Amendment

(1) The words "a digital encoding method of digital encoding means is switched to a digital encoding method suitable for the facsimile modulating method," appear in lines 14 to 17 on page 10 should be deleted.

(2) The words "the digital encoding method that is optimum to the facsimile modulating method is selected and" which appear in lines 4 to 6 on page 11 should be deleted.

(3) The words "of high reliability" in lines 6 to 7 on page 11 should be deleted.

(4) The words "the digital encoding method of said digital encoding means is switched to a digital encoding method suitable for said facsimile modulating method," which appear in lines 23 to 25 on page 49 should be deleted.

(5) The words "the digital encoding method of said digital encoding means is switched to a digital encoding method suitable for said facsimile modulating method," appears in lines 19 to 22 on page 51 should be deleted.

(6) The words "the digital encoding method of said digital encoding means is switched to a digital encoding method suitable for said facsimile modulating method," appears in lines 17 to 19 on page 53 should be deleted.

(7) New claims 13 through 15 should be added.

6. List of Attached Documents

(1) Replacement sheets of pages 10, 11, 49 to 54 and 54-1

if the opponent station has an IP address, there is selected a first image communicating procedure by which the image data is not facsimile-modulated but sent and received to/from the opponent station on an IP network on the basis of a predetermined IP communication protocol by using the IP address of the opponent station obtained from a predetermined server on the basis of a telephone number of the opponent station, and

10 if the opponent station does not have the IP address, there is selected a second image communicating procedure by which the image data is facsimile-modulated by a predetermined facsimile modulating method, an analog facsimile signal

15 obtained by the facsimile modulation is digitally encoded by the digital encoding means, and subsequently, the digital coded signal is sent to the opponent station through a media gateway for executing analog/digital signal conversion between

20 the IP network and a public line network.

By using the characteristic construction as mentioned above, according to the invention, the following advantages are obtained: a large amount of image data can be sent to the opponent station at a

high speed by using the first image communicating procedure without using the facsimile procedure, and when the image communication is made by the second image communicating procedure, the image
5 communication can be made with the opponent station through the media gateway.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing a
10 construction of a network system including image communicating apparatuses using the invention.

Fig. 2A is a block diagram showing an internal construction of the image communicating apparatus using the invention.

15 Fig. 2B is a block diagram showing an internal construction of a conventional image communicating apparatus.

Fig. 3A is an explanatory diagram showing a communication sequence for sending an image from an
20 image communicating apparatus 104 in Fig. 1 to an image communicating apparatus 107.

Fig. 3B is an explanatory diagram showing a communication sequence for sending an image from the image communicating apparatus 104 in Fig. 1 to an
25 image communicating apparatus 112.

CLAIMS

1. (amended) A communicating apparatus for digitally encoding a speech signal by digital encoding means and sending the coded signal to an opponent station, thereby making VoIP speech communication and sending and receiving image data to/from the opponent station, comprising:
 - communication control means for, when image data is sent to the opponent station,
 - 10 if the opponent station has an IP address, selecting a first image communicating procedure by which the image data is not facsimile-modulated but sent and received to/from the opponent station on an IP network on the basis of a predetermined IP
 - 15 communication protocol by using the IP address of the opponent station obtained from a predetermined server on the basis of a telephone number of the opponent station, and
 - if the opponent station does not have the IP
 - 20 address, selecting a second image communicating procedure by which the image data is facsimile-modulated by a predetermined facsimile modulating method, an analog facsimile signal obtained by said facsimile modulation is digitally encoded by said
 - 25 digital

encoding means, and subsequently, the digital coded signal is sent to the opponent station through a media gateway for executing analog/digital signal conversion between the IP network and a public line network.

2. A communicating apparatus according to claim 1, wherein in said second image communicating procedure, the digital encoding method of said digital encoding means is switched to the digital encoding method suitable for said facsimile modulating method, and a tone signal necessary for a facsimile communication procedure or the facsimile-modulated transmission image data is inputted to said digital encoding means.

3. A communicating apparatus according to claim 1, wherein when the image data is sent to the opponent station, which one of said first and second image communicating procedures is used is determined by analyzing the telephone number of the opponent station.

4. A communicating apparatus according to claim 1, wherein in said VoIP speech communication, the digital encoding method of said digital encoding means is selected on the basis of negotiation which is performed on the basis of a VoIP protocol.

5. (amended) A control method of a communicating apparatus for digitally encoding a speech signal by

digital encoding means and sending the coded signal to an opponent station, thereby making VoIP speech communication and sending and receiving image data to/from the opponent station, wherein:

- 5 when image data is sent to the opponent station, if the opponent station has an IP address, there is selected a first image communicating procedure by which the image data is not facsimile-modulated but sent and received to/from the opponent station on an
- 10 IP network on the basis of a predetermined IP communication protocol by using the IP address of the opponent station obtained from a predetermined server on the basis of a telephone number of the opponent station, and
- 15 if the opponent station does not have the IP address, there is selected a second image communicating procedure by which the image data is facsimile-modulated by a predetermined facsimile modulating method, an analog facsimile signal
- 20 obtained by said facsimile modulation is digitally encoded by said digital encoding means, and subsequently, the digital coded signal is sent to the opponent station through a media gateway for executing analog/digital signal conversion between

the IP network and a public line network.

6. A control method of the communicating apparatus according to claim 5, wherein in said second image communicating procedure, the digital
5 encoding method of said digital encoding means is switched to the digital encoding method suitable for said facsimile modulating method, and a tone signal necessary for a facsimile communication procedure or facsimile-modulated transmission image data is
10 inputted to said digital encoding means.

7. A control method of the communicating apparatus according to claim 5, wherein when the image data is sent to the opponent station, which one of said first and second image communicating
15 procedures is used is determined by analyzing the telephone number of the opponent station.

8. A control method of the communicating apparatus according to claim 5, wherein in said VoIP speech communication, the digital encoding method of
20 said digital encoding means is selected on the basis of negotiation which is performed on the basis of a VoIP protocol.

9. (amended) A control program of a communicating apparatus for digitally encoding a speech signal by
25 digital encoding means and sending the coded signal to an opponent station, thereby making VoIP speech communication and sending and receiving image data

to/from the opponent station, comprising:

a control step of, when image data is sent to the opponent station,

if the opponent station has an IP address,

- 5 selecting a first image communicating procedure by which the image data is not facsimile-modulated but sent and received to/from the opponent station on an IP network on the basis of a predetermined IP communication protocol by using the IP address of the
- 10 opponent station obtained from a predetermined server on the basis of a telephone number of the opponent station, and

- if the opponent station does not have the IP address, selecting a second image communicating
- 15 procedure by which the image data is facsimile-modulated by a predetermined facsimile modulating method, an analog facsimile signal obtained by said facsimile modulation is digitally encoded by said digital encoding means, and subsequently, the digital
- 20 coded signal is sent to the opponent station through a media gateway for executing analog/digital signal conversion between the IP network and a public line network.

10. A control program of the communicating

apparatus, according to claim 9, wherein in said second image communicating procedure, the digital encoding method of said digital encoding means is switched to the digital encoding method suitable for said facsimile modulating method, and a tone signal necessary for a facsimile communication procedure or facsimile-modulated transmission image data is inputted to said digital encoding means.

11. A control program of the communicating apparatus, according to claim 9, wherein when the image data is sent to the opponent station, which one of said first and second image communicating procedures is used is determined by analyzing the telephone number of the opponent station.

12. A control program of the communicating apparatus, according to claim 9, wherein in said VoIP speech communication, the digital encoding method of said digital encoding means is selected on the basis of negotiation which is performed on the basis of a VoIP protocol.

13. (new) A communicating apparatus according to claim 1, wherein in the second image communication procedure, said communication control means switches the digital encoding method of said digital encoding means to a digital encoding method suitable for said facsimile modulating method, and causes said digital encoding means to digitally encode an analog

facsimile signal obtained by said facsimile modulation.

14. (new) A control method of communicating apparatus according to claim 5, wherein in the second
5 image communication procedure, the digital encoding method of said digital encoding means is switched to a digital encoding method suitable for said facsimile modulating method, and said digital encoding means
10 digitally encodes an analog facsimile signal obtained by said facsimile modulation.

15. (new) A control program of communicating apparatus according to claim 9, wherein in the second image communication procedure, the digital encoding method of said digital encoding means is switched to
15 a digital encoding method suitable for said facsimile modulating method, and said digital encoding means digitally encodes an analog facsimile signal obtained by said facsimile modulation.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.